

R H B 37 E

Resistor
None - No Resistor
R - Mil-Spec. Resistor
 Erosion Protection

Electrode Design
None - Conventional Single
E - Two Electrode Massive
N - Four Electrode Massive
S - Single Electrode (Iridium)
B - Twin Electrodes(Nickel)
R - Push-wire - 90° to Center
Y - Projected Core Nose
P - Two Electrode (Platinum)
W - Two Electrode (Iridium)

Barrel Style
None - Unshielded
E - Shielded 5/8" - 24 Thread
H - Shielded 3/4" - 20 Thread
 (All-Weather Plug)
V - M18X1 - Metric

Heat Rating Position
High Number - Hot (50)
Low Number - Cold (26)

Mounting Thread

B- 18 mm
M- 18 mm
J- 14 mm
L- 14 mm
U- 18 mm
N- 14 mm

Reach

13/16" (2.06 cm)
 1/2" (1.27 cm)
 3/8" (.095 cm)
 1/2" (1.27 cm)
 1-1/8" (2.85 cm)
 3/4" (1.90 cm)

Hex Size

7/8" (2.22 cm)
 7/8" (2.22 cm)
 13/16" (2.06 cm)
 13/16" (2.06 cm)
 7/8" (2.22 cm)
 13/16" (2.06 cm)